



























# **NAN YA ASTM UPVC PIPE** Not being fouled easily, lightweight, our pipes have reasonable price and high durability

#### **Features**

- Low fluid resistance, high mechanical strength and excellent electrical insulation, no effect on water quality.
- Easy and speedy construction with lower costs than that of metal piping.
- Standardized manufacturing process leading to stable quality.
- Fittings with various sizes and complete specifications.
- Used as high-pressure piping for electronic factory.






## **∠** Color






# **Specifications**

Items	Outer Diameter
SCH40, SCH80 UPVC PIPES	3/8"~24"
SCH120 UPVC PIPES	1/2"~12"
SCH40, SCH80 CPVC PIPES	3/8"~16"



Note: With better physical properties than those of other materials, Nan Ya UPVC pipe is the leading brand in the market.

#### **Product Component Features**



-

# Factory Locations Chiayi, Xiamen

Contact Information NAN YA Plastics Corp. Plastics 3nd Div. Sales 1st Dept.


TEL: 886-2-27178230 FAX: 886-2-25140628

ADD.: 3F., No.201, Dunhua N. Rd., Songshan Dist.,

Taipei City 10508, Taiwan E-mail: 23M10@npc.com.tw

# **NAN YA HDPE PIPE**

Earthquake resistance of magnitude 8, not being fouled easily, excellent ductility, service life up to 97 years.



#### **Features**

- Cold, earthquake, and impact resistance.
- Excellent elongation and bending flexibility reduce connecting points and leakage.
- Resistant to acid, alkali, and chemicals and applicable to chemical and seawater transport.
- Food-grade product suitable for the transportation of milk and cooking oil.






## **∠** Color



#### **Specifications**

Outer diameter: 16 mm ~ 800mm



Note: With better physical properties than those of other materials, Nan Ya HDPE pipe is the leading brand in the market.

#### **Product Component Features**

Elongation at breaking up to 350 ~ 1,000% (about 6~16.6 times higher than that of stainless steel). Made of high- quality HDPE raw materials. Resistant to cold (-40°C), acid, and alkali.



Roughness coefficient: 0.009. (smooth surface with low fluid resistance and no fouling)

Factory Locations Chiayi, Xiamen, Guangzhou, Zhengzhou

Contact Information NAN YA Plastics Corp. Plastics 3nd Div. Sales 1st Dept.

TEL: 886-2-27178230 FAX: 886-2-25140628


ADD.: 3F., No.201, Dunhua N. Rd., Songshan Dist., Taipei City 10508, Taiwan

E-mail: 23M10@npc.com.tw

ද්ද

C) A


CNS 2456-2, 14571, 14572



#### **Features**

- Used for chemical industry with excellent acid, alkali, and corrosion resistance.
- Suitable for a wide range of piping projects with excellent hydraulic, external pressure, and impact resistance.
- Resistant to acid, alkali, and chemicals and applicable to chemical and seawater transport.
- Best choice for water supply piping without effect on water quality.
- Unplasticized and lead-free electrical conduit products meeting requirements related to green energy.
- Lightweight, convenient for moving, loading, unloading, and construction.

# ≥ Style / Colors








# **Specifications**

Items	Outer diameter
Drainage pipe	3/8"~24"
Water supply pipe	3/8"~24"
Water supply pipe	3/8"~8"



# **Product Component Features**

External Surface:

About 150% elongation rate (about 2.5 times than that of stainless steel), using high-quality PVC raw materials with features of being acid-resistant and alkali-resistant



Roughness coefficient: 0.009 (smooth surface with low fluid resistance and no fouling)

Factory Locations Chiayi, Xiamen, Guangzhou, Zhengzhou

Contact Information NAN YA Plastics Corp. Plastics 3nd Div. Sales 1st Dept.

TEL: 886-2-27178230 FAX: 886-2-25140628

ADD.: 3F., No.201, Dunhua N. Rd., Songshan Dist., Taipei City 10508, Taiwan

E-mail: 23M10@npc.com.tw

ch ch

CNS4053-1, CNS1298, CNS1302

# NAN YA PVC-DWV FOAM CORE PIPE



#### **Features**

- Low drainage noise (about 5 decibels).
- Excellent resistance to acid, alkali, and corrosion.
- Flattening, rigidity, and impact tests are in compliance with ASTM and CNS standards.
- Suitable for sewage and drainage piping of buildings.
- Fittings with various sizes and complete specifications.






#### **∠** Colors





#### **Specifications**

Outer Diameter: 1 1/2 inch ~ 8 inch




※ Nan Ya pipes are the leading brand in the market, and the characteristics of DWV Foam Core pipes are also superior to other materials

## **Product Component Features**

#### ➤ External Surface:

With a density of 0.95~1.0 (about 1/8 of the cast iron pipe), they are light weight as well as easy to handle and install by using high-quality PVC raw materials with high acid and alkali resistance



#### ► Internal Surface:

Internal Surface: Roughness Coefficient: 0.009(Smooth surface with low fluid resistance and no fouling)

# Factory Locations Chiayi

Contact Information NAN YA Plastics Corp. Plastics 3nd Div. Sales 1st Dept.

TEL: 886-2-27178230 FAX: 886-2-25140628

ADD.: 3F., No.201, Dunhua N. Rd., Songshan Dist., Taipei City 10508, Taiwan

E-mail: 23M10@npc.com.tw

# **NAN YA HT-CPVC PIPE**



#### **Features**

- Superb thermal resistance; suitable for hot water piping (93°C ↓).
- Good hydraulic resistance, external pressure resistance, and impact resistance.
- Excellent acid, alkali, and corrosion resistance.
- Smooth internal surface with low fluid resistance.
- The pipes are lightweight, convenient for moving, loading, unloading, and construction.
- Applicable to piping for household, hotel, hot spring, and chemical industry.



#### **∠** Colors









#### **Specifications**

Outer Diameter: 3/8 inch ~ 16 inch



Nan Ya pipes are the leading brand in the market, the characteristics of CPVC pipes are also superior to other materials

#### **Product Component Features**



## Factory Locations Chiayi

Contact Information NAN YA Plastics Corp. Plastics 3nd Div. Sales 1st Dept.

TEL: 886-2-27178230 FAX: 886-2-25140628

ADD.: 3F., No.201, Dunhua N. Rd., Songshan Dist., Taipei City 10508, Taiwan

E-mail: 23M10@npc.com.tw

# NAN YA HI HIGH-IMPACT PVC PIPE



#### **Features**

- Exceptionally excellent impact resistance with great flexibility, and earthquake resistance.
- Lightweight, convenient to move, load, unload, and install as well as manpower saving.
- Used for chemical industry with excellent acid, alkali, and corrosion resistance.
- Not effect on water quality.






#### **∠** Colors



#### **Specifications**

Outer Diameter: 3/8 inch ~ 16 inch



Nan Ya pipes are the leading brand in the market, and the characteristics of HI High-Impact pipes are also superior to other materials.

## **Product Component Features**

#### → External Surface:

About 150% elongation rate (about 2.5 times than that of stainless steel), using high-quality and impact-resistant PVC raw materials with features of being anti-seismic, acid-resistant, and alkali-resistant



#### ➤ Internal Surface:

Roughness Coefficient: 0.009 (Smooth surface with low fluid resistance and no fouling)

Factory Locations Chiayi

Contact Information NAN YA Plastics Corp. Plastics 3nd Div. Sales 1st Dept.

TEL: 886-2-27178230 FAX: 886-2-25140628

ADD.: 3F., No.201, Dunhua N. Rd., Songshan Dist., Taipei City 10508, Taiwan

E-mail: 23M10@npc.com.tw

Ch Ch

CNS14345